

Over 110 Years of Quality
Your partner in energy saving!




Inverter Split Wall Mounted Type

R410a



World renowned since 1906

Say ¥€\$ to COP




3 or 4-Bend Heat Exchanger



Trapeziform Innergroove



Gold Fin Condenser



Hydrophillic Aluminium



Anti-Rust Cabinet



Quiet Operation



Easy-Cleaned Panel



Auto-Restart Function



Self-diagnosis and Auto-protection



Multilayer dustproof filter

Model		Indoor	WM03LHNI	WM04LHNI	WM06LHNI	WM08LHNI
		Outdoor	HP09MLNI	HP12MLNI	HP18MLNI	HP24MLNI
Capacity						
Cooling	(Min - Max)	Btu/h	1740 - 9180	2320 - 12389	5732 - 18181	13276 - 24164
		kW	0.50 - 2.68	0.67 - 3.63	1.67 - 5.32	3.89 - 7.08
Heating	(Min - Max)	Btu/h	1500 - 9600	2000 - 13000	5323 - 19005	8189 - 23000
		kW	0.43 - 2.81	0.58 - 3.80	1.55 - 5.57	2.39 - 6.73
Electrical						
Voltage/Frequency/Phase		V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50
Power Input	Cooling	W	200 - 825	220 - 1090	470 - 1640	650 - 2010
Power Input	Heating	W	200 - 775	220 - 1050	420 - 1540	600 - 1870
Rated Current	Cooling	A	3.66 - 6.3	4.84 - 6.9	7.28 - 10.86	8.9 - 11
Rated Current	Heating	A	3.44 - 6.9	4.66 - 7.3	6.83 - 11.09	8.3 - 12
Performance						
EER		W/W	3.19	3.23	3.21	3.21
COP		W/W	3.61	3.62	3.62	3.61
Indoor Airflow	(Hi/Med/Low)	m ³ /h	490/430/330	540/460/330	800/700/570	1000/950/850
Noise Level	(Hi/Med/Low)	dB(A)	45/32/28	47/43/39	53/49/45	56/52/48
Net Dimensions & Weight						
Indoor Unit	W x H x D	mm	790x275x200	845x289x209	970x300x224	1078x325x246
Outdoor Unit	W x H x D	mm	670x528x195	670x528x195	899x596x378	965x700x396
Net Weight	Indoor / Outdoor	kg	9 / 28	11 / 30	13.5 / 41	16 / 46
Packaging Dimensions & Gross Weight						
Indoor Unit	W x H x D	mm	866x367x271	921x379x281	1041x383x320	1148x413x350
Outdoor Unit	W x H x D	mm	710x550x318	710x550x318	948x645x420	1029x750x458
Gross Weight	Indoor / Outdoor	kg	11 / 30	13 / 32	16.5 / 44.5	19.5 / 51
Piping Connections						
Liquid Side	(HP)	mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
Gas Side	(LP)	mm (inch)	9.53 (3/8")	9.53 (3/8")	12.7 (1/2")	15.2 (5/8")
Max Pipe Length		m	20	20	25	25
Max Pipe Height		m	10	10	10	10

Remarks: Cooling capacities are based on indoor air temp. 27°C DB, 19°C WB and outdoor air temp. 35°C DB, 24°C WB. The above specifications are subject to change without prior notice for product improvement.



Dunham-Bush International (Africa) (Pty) Ltd
 57 Sovereign Drive
 Route 21 Corporate Park
 Irene SOUTH AFRICA
 Tel: +27 12 345 4202
 Fax: +27 12 345 4203
 PO Box 1431 Wingate Park
 0153 SOUTH AFRICA
 e-mail: info@dunham-bush.co.za



08611ASKDB